

AST Catalog

For the Most Complete & Up-to-Date Product Information Please Visit Us at www.universalvalve.com



478 Schiller St • Elizabeth, NJ 07206 1-800-223-0741 • (F) 1-800-443-8258 • sales@universalvalve.com









Say Hello to Galvanneal Island Forms!

Galvanneal with a primer coating gives you far better protection from rust then standard sheet metal!

Now Universal offers two great options for superior element protection as a standard!

Galvanneal with black primer, so you can paint your islands to match the color of the stores decor! Stainless Steel for that clean low

maintenance option.

Bundle your order with the u-shape guards and save even more!

Universal Valve Island Forms Are Available with These Features:

- 6" Radius Corners
- Full Radius Ends
- Full Radius Ends w/Bumpers
- Bow Tie Islands
- Curbing

- Galvanneal w/ Black Primer
- Stainless Steel
- 12 gauge
- Endless widths and lengths
- Pre-assembled 1 Piece
- Standard breakdown Islands

Be Sure, Be Safe, Choose Universal!

For other sizes and options Call for a quote today: 800-223-0741







MODEL 49 OVERFILL VALVE UST/AST

UL approved for both Pressure and Gravity fills!

Universal Valve: Model 49, protects against gravity filling into a typical "AST Tank". If you have installed an "AST Tank" in a basement or below the grade of the fill point and you gravity fill, you could be at risk of an overfill. Universal is UL approved for both Pressure Fill and gravity fill with no minimum flow rate!

- UL Approved for Pressure and Gravity Fills
- No minimum flow rate
- 1 part number for direct or remote fills
- Available in an E-85 and B-100 versions
- Built and tested in the U.S.A.!

Be Sure, Be Safe, Choose Universal!



Universal Valve Co., Inc.
478 Schiller St—Elizabeth, NJ 07206
800-223-0741
www.universalvalve.com






TYPICAL ABOVE GROUND TANK APPLICATION

A Complete Line of Valves, Fittings, Accessories and Manholes for Your Installation.

Universal offers you the widest selection of Valves, Fittings, Accessories, and Manholes in the industry. These quality products provide proven performance with today's industry regulations and specifications.

Note: The drawing shows only general locations of various Universal products contained in this catalog. The products are not shown in actual size or proportion to Universal, or other products listed.





E-85 AST TANK DRAWING



45 2" Vent

46 2" Pressure Vacuum Vent

48 4", 6", 8" Tank Vent


E-49 Pressure Fill Overfill Valve

76CD Spill Container
76M Spill Container
E-403 Anti-Syphon Valve
521KR Shear Valve Mount

E-723 Drop Tube

High Hose Retriever

0611V Vapor Adapter 0613VC Orange Vapor Cap



ABSORBENTS

The Ultimate 20 Gallon Emergency Spill Response Kit

UN approved water and chemical resistant polyethylene container with leak proof twist on lid. Equipped with Universal absorbent products. Absorbs up to 15.2 gallons.

| Part Number | Size |
|-------------|---|
| 2005-SKA-20 | (25) 15" x 19" Pads (4) 3" x 4' Socs (2) 18" x 18" Pillows (1) Safety Goggles (1) Pair Nitrile Gloves (4) Disposable Bags & Ties (6) Tamper Proof Seals |
| | Shipping Dimensions: 23" w x 23" L x 19" H 23.2 lbs |



The Ultimate 55 Gallon Emergency Spill Response Kit

UN approved water and chemical resistant polyethylene container with ring clamp top lid. Equipped with Universal absorbent products. Absorbs up to 51.9 gallons.

| Part Number | Size |
|-------------|---|
| 2005-SKA-55 | (100) Pads (15" x 19") (10) Socks (3" x 4') (5) Pillows (18" x 18") (2) Pair Safety Goggles (4) Disposal Bags & Ties (1) Emergency Response Guidebook (2) Pair Nitrile Gloves (6) Tamper Proof Seals Shipping Dimensions: 24" w x 24" L x 40" H 55.5 lbs |



ABSORBENTS

Slikwik Socs™

Specialized oil-only polypropylene SOC for use against oil and petroleum based spills.

| Part Number | Size | Quantity |
|-------------|----------|----------|
| 2005-OIL412 | 3" x 4' | 10/case |
| 2005-OIL124 | 3" x 12' | 10/case |



Env™ Oil Sorbents

Economical contractor grade pads for oil clean up.

| Part Number | Size | Quantity |
|-------------|----------------------------|--------------|
| 2005-ENV200 | 15" x 19" Medium weight | 200 per bale |
| 2005-ENV300 | 15" x 19" Medium weight | 100 per bale |
| | *OIL ONLY* | |



Slikwik Pillows

Absorbent Slikwik Pillows meet a varity of cleanup and safety needs. Excellent for absorbing spills and leaking fluids in tight spaces.

| Part Number | Size | Quantity |
|----------------|-----------|----------|
| 2005-OIL1818-2 | 18" x 18" | 8/case |
| 2005-AW1818-2 | 18" x 18" | 8/case |



[&]quot;*Allwik spill kits are suitable for all-purpose maintenance and spills." "*Oil only spill kits will absorb only oil. No water or water based solutions."

VAPOR VENTS

UPFLOW VENT

Application -

Assures even pressure in the UST/AST during filling or dispensing

Part Number - 45





Only from Universal! – Designed with an upward flow to rapidly disperse vapors. A grooved drain lip in the cap allows for efficient water drain-off.

Features -

- ✓ All cast metal construction
- ✓ Easy installation with 2 set screws
- ✓ Flame retardant 40 mesh bronze screen
- ✓ Conforms with NFPA-30


Construction -

- · All metal body
- · Bronze screen

| Pipe Size | Weight (Ibs.) | Α | B 45-15 |
|-----------|---------------|----------------------|------------------------------------|
| 1-1/2" | 1.2 | 4-3/8" | 4" |
| 2" | 1.1 | 4-3/8" | 4" |
| 3" | 2.6 | 5-3/8" | 6" |
| | 1-1/2" 2" | 1-1/2" 1.2 2" 1.1 | 1-1/2" 1.2 4-3/8" 2" 1.1 4-3/8" |

Replacement Parts

| Part Numbers | Description |
|--------------|-----------------------------------|
| 45-1-A | 2" x 1 1/2" Bushing (Model 45-15) |
| 45-2-E | 2" Body Screw |
| 45-3-E | 3" Body Screw (Model 45-30) |





VAPOR VENTS

PRESSURE VACUUM VENT

Application -

Vapor recovery applications to assure even pressure in the UST during filling or dispensing.

Part Number - 46





Only Universal provides rugged all cast metal construction...built to last. This eliminates any injuries due to sharp corners and edges, unlike competitive fabricated products.


Features -

- Restricts vapor escape during product drops
- ✓ Vent slips onto existing vent piping and is held in place by 3 set screws (Model 46-2080 has 2" NPT threads)
- CARB certified
- ✓ Conforms with NFPA-30
- ✓ Compatible with E-85

Construction -

- · All cast aluminum body
- · Flame retardant 40 mesh bronze screen

| | | Weight | | | Vacuu | m |
|-----------|------|--------|-----------------|--------|---------------|------|
| Model | Size | (lbs.) | Α | В | Pressure | {oz} |
| 46CS-2080 | 2" | 2 | 5-7/8" | 4-1/4" | 2" Water Col. | 0.5 |
| 46CS-3080 | 2" | 2 | 5 - 7/8" | 4-1/4" | 3" Water Col. | 0.5 |
| 46-2080 | 2" | 2 | 5 - 7/8" | 4-1/4" | 8 oz. | 0.5 |
| 46S-2080 | 2" | 2 | 5 - 7/8" | 4-1/4" | 8 oz. | 0.5 |
| 46P-3L | 3" | 3.5 | 6" | 4-1/4" | 2" Water Col. | 0.5 |



Replacement Parts

| Part Numbers | Description | |
|--------------|---------------------------------------|--------|
| 200A-15-H | Cotter Pin | sizo |
| 45-20 | 2" Upflow Vent | SIZE → |
| 45-2-E | 2" Body Screw | |
| 46-2-A | 2" Body NPT (Model 46-2080) | |
| 46-2-G | Gasket (Model 46) | |
| 46C-2-B | 2" Body w/o Threads (Models 46CS,46S) | |
| 46C-2-G | Gasket (Model 46CS) | |
| 46C-2-J | Cone Spring (Model 46CS-2080) | |

OVERFILL PROTECTION

2" NPT OVERFILL VALVE

Application -

All new 2" overfill valve. The new 47-20 fits 2" tank openings. With no minimum flow rate this valve can be used for a wide variety of applications.

Part Number - 47-20



Features -

- ✓ No minimum flow rate to operate
- ✓ No line shock, gradual shut-off
- ✓ No float hang up
- Prevents overfills in tanks reducing contamination and costly clean-up
- ✓ Completely automatic operations
- ✓ Easily retrofitted to existing tanks
- 2" NPT tank opening
- ✓ 55gpm at 30PSI
- ✓ 10PSI = 100gpm
- ✓ Max 100PSI
- ✓ Max 150 Centistokes


Construction -

- · Hard coated aluminum
- · Reinforced closed cell float
- Buna gaskets

| Model# | Weight | (lbs.) |
|--------|--------|--------|
| 47-20 | _ | 1 86 |



Only Universal Valve offers a 2" overfill valve designed to operate with no minimum flow rate. Making this valve the most versatile overfill on the market.



Replacement Parts

| Part Numbers | Description_ | | |
|---------------|--------------|--|--|
| 47 - F | Float | | |
| 47 - G | Float Rod | | |



OVERFILL PROTECTION

UST WASTE OIL OVERFILL VALVE

Application -

The new 47-20-USTWO fits 4" tank openings.

With no minimum flow rate this valve can be used for a wide variety of applications.

Part Number - 47-20-USTWO



47-20-USTWO Includes: Fill Cap (not shown) Fill Adapter 4" Adapter Coupling 47-20 Overfill Valve

Not included: Internal Riser Pipecontractor supplied length TBD by installation instructions

Features -

- ✓ No minimum flow rate to operate
- ✓ No line shock, gradual shut-off
- ✓ No float hang up
- ✓ Prevents overfills in tanks reducing contamination and costly clean-up
- ✓ Completely automatic operations
- ✓ Easily retrofitted to existing tanks
- 4" NPT tank opening
- ✓ 55gpm at 3OPSI
- ✓ 10PSI = 100gpm
- ✓ Max 100PSI
- ✓ Max 150 Centistokes

Replacement Parts Part Number Description

49-C 2" Fill Adapter 49-CAP 2" Fill Cap

Optional funnel

49-D 2"x 4" Adapter Coupling 47-USTF UST Waste Oil Funnel

Construction -

- Hard coated aluminum
- · Reinforced closed cell float
- Buna gaskets

Model#

Weight (lbs.)

47-20-USTWO UST Waste Oil Overfill Valve 5.6 lbs
47-20-USTWOF UST Waste Oil Overfill valve w/ Funnel 6,9 lbs

Notice: Universal Valve Co., products must be used in compliance with applicable federal, state, and local laws and regulations. Product selection should be based on physical specifications and limitations and compatibility with the environment and material to be handled. Universal Valve Co., makes no warranty of fitness for a particular use. All illustrations and specifications in this literature are based on the latest production information available at the time of publication. Prices, materials, and specification are subject to change at any time, and models may be discontinued at any time, in either case, without notice or obligation.

UNIVERSAL VALVE COMPANY




AST EMERGENCY VENTS

BLOW OFF VENTS

Application -

For all AST storage applications. Allows venting to relieve the excessive internal pressure build-up. The emergency vents will open at approximately 1 PSI.

Part Number - 48





Only from Universal! —The unique mushroom design specifically prevents water and contaminants from entering the AST.


Features -

- ✓ O-ring seal prevents vapor leaks
- ✓ Mounts onto the tank
- ✓ Female threads
- ✓ Non-corrosive polymeric coating
- ✓ Meets state and federal regulations
- ✓ Compatable with E-85

Construction -

· Rugged epoxy coated cast iron body

| Model | Thread Size | Weight (lbs.) | CFH Chart | A | В |
|--------|----------------|---------------|-----------|--------|---------|
| 48-40 | 4" | 18.8 | 119,750 | 6" | 7-1/2" |
| 48-60 | 6" | 30 | 246,130 | 6" | 10" |
| 48-80 | 8" | 39 | 462,000 | 6" | 12-1/2" |
| 48M-40 | 4" Male | 20.3 | 119,750 | 6-1/4" | 7-1/2" |
| 48M-60 | 6" Male | 31.5 | 462,000 | 6-1/4" | 10-1/4" |
| | | | | | |







OVERFILL PROTECTION VALVES

AST/UST VALVE


Application -

Prevent overfills in AST's and UST's.

Part Number - 49



The best overfill protection available today. No line shock and gradual shut-off to eliminate any stress on the system.



U.L. Approved for both Pressure and Gravity Fill Applications. No Minimum Flow Rate Required.

Features -

- ✓ No line shock, gradual shut-off design
- ✓ No stress on system
- ✓ No float hang-up
- Prevents overfills reducing contamination and costly clean-up
- ✓ Completely automatic operation
- ✓ Easily retro-fitted to existing tanks
- Shipped with fill adapter
- ✓ Adjustable collar provides simple installation
- Minimal pressure drop
- ✓ Compatible with E-85 (Model E-49)

Construction -

- · Hard coated aluminum pipe adapter
- · Zinc plated steel linkage
- · Reinforced closed cell float

| | Fill Adapter | Weight | | | |
|---------|--------------|--------|---------|----------|----------|
| Model | Size | (lbs.) | Α | В | <u> </u> |
| 49-02 | 2" | 10.0 | 22-3/8" | 3-11/16" | 15-3/4" |
| 49-03* | 3" | 10.0 | 22-3/8" | 3-11/16" | 15-3/4" |
| E-49-02 | 2" | 10.0 | 22-3/8" | 3-11/16" | 15-3/4" |
| E-49-03 | 3" | 10.0 | 22-3/8" | 3-11/16" | 15-3/4" |

49-DTC attaches standard 2" Aluminum Drop Tube (sold separately)

49-Cap 2" Fill Cap (sold separately)

Replacement Parts

| Description |
|-------------------------------|
| 3x2 Adapter |
| 2" Fill Adapter (Model 49-02) |
| 2" Dust Cap (Model 49-02) |
| 2" x 4" Adapter (Model 49-02) |
| Adapter O-Ring (Model 49-02) |
| Float (Model 49-02) |
| 2" x 12" Nipple (Model 49-02) |
| |

^{*}Model 49-03 is a 49-02 with a 3" fill coupler.



BALL VALVES

FULL PORT

Application -

Allows easy line shut off, which prevents system shut-down during maintenance.

Part Numbers - 213FP



Features -

- ✓ Allows easy line testing
- ✓ Rugged brass body
- ✓ Compatible with E-85 (Model SS)

Construction -

- Stainless steel ball with Teflon seals
- Brass body
- · Plastic coated handle

| Model | Size | | |
|--------------|---|--------------|---|
| 213FP-025 | 1/4" Brass Ball Valve | Model | Size |
| 213FP-025-L | 1/4" Brass Ball Valve Locking | 213FP-20 | 2" Brass Ball Valve |
| 213FP-0375 | 3/8" Brass Ball Valve | 213FP-20-L | 2" Brass Ball Valve Locking |
| 213FP-0375-L | 3/8" Brass Ball Valve Locking | 213FP-20SS | 2" Stainless Steel Ball Valve Locking |
| 213FP-050 | 1/2" Brass Ball Valve | 213FP-25 | 2-1/2" Brass Ball Valve |
| 213FP-50-L | 1/2" Brass Ball Valve Locking | 213FP-30 | 3" Brass Ball Valve |
| 213FP-50-SS | 1/2" Stainless Steel Ball Valve Locking | 213FP-40 | 4" Brass Ball Valve |
| 213FP-10 | 1" Brass Ball Valve | 213FP-750 | 3/4" Brass Ball Valve |
| 213FP-10-L | 1" Brass Ball Valve Locking | 213FP-750-L | 3/4" Brass Ball Valve Locking |
| 213FP-10-SS | 1" Stainless Steel Ball Valve Locking | 213FP-750-SS | 3/4" Stainless Steel Ball Valve Locking |
| 213FP-125 | 1-1/4" Brass Ball Valve | | · · |
| 213FP-125-L | 1-1/4" Brass Ball Valve Locking | | |
| 213FP-15 | 1-1/2" Brass Ball Valve | | |
| 213FP-15-L | 1-1/2" Brass Ball Valve Locking | | |
| 213FP-15-SS | 1-1/2" Stainless Steel Ball Valve | | |



ANGLE CHECK VALVES


SUCTION SYSTEMS

Application -

Holds the prime in suction systems.

Part Number - 401





Features -

- ✓ Ultra precise machined bronze seat and poppet for effectively holding the prime
- Cast iron body that eliminates any distortion of the valve seat while tightening


Construction -

- · Zinc plated cast iron body
- · Precision bronze seat and poppet

| | Thread | | | | |
|--------|---------|---------------|--------|--------|---|
| Model | Size | Weight (lbs.) | Α | В | |
| 401-15 | 1-1/12" | 4.6 | 4-5/8" | 4" | _ |
| 401-20 | 2" | 7.2 | 5-1/4" | 5-1/8" | |

Replacement Parts

| Part Numbers | Description |
|--------------|-------------|
| 401-15BC | 1-1/2" Cap |
| 401-20BC | 2" Cap |



ABOVE GROUND TANK VALVES

ANTI-SYPHON VALVE

Application -

Reducing fire hazards and preventing fuel spillage should a line rupture.

The flow would automatically stop the syphon effect.

*Also available with pressure relief for thermal expansion (403PR).

Part Number - 403



Features -

- ✓ Precision machined valve seats
- ✓ Automatic shut off syphon effect

Thread

- ✓ Prevents fuel spillage
- ✓ No need to specify head settings when ordering

Weight


✓ PR opens 15-35PSI



Only from Universal! - No need to specify head settings! Everything is included to cover an operating range of 0' to 20'.

Construction -

- Zinc plated cast iron body
- Buna-N seals



| Replacement |
|-------------|
| Parts Part |
| Numbers |

| Model | Size | (lbs.) | Α | В | Numbers |
|----------|--------|--------|--------|--------|------------|
| 403-34 | 3/4" | 5.0 | 4-3/4" | 2-3/8" | 403-10-A |
| 403PR-34 | 3/4" | 5.0 | 4-3/4" | 2-3/8" | |
| 403-10 | 1" | 4.8 | 4-3/4" | 2-3/8" | 403-15-E |
| 403PR-10 | 1" | 4.8 | 4-3/4" | 2-3/8" | 403-15-SK |
| 403-15 | 1-1/2" | 4.6 | 4-3/4" | 2-3/8" | 403-20-SK |
| 403PR-15 | 1-1/2" | 4.6 | 4-3/4" | 2-3/8" | 403-34-A |
| 403-20 | 2" | 7.2 | 5-3/8" | 2-1/2" | 403-15-CAP |
| 403PR-20 | 2" | 7.2 | 5-3/8" | 2-1/2" | 403-20-CAP |

Description

1-1/2" x 1" Reducer Bushing Poppet Guide Spring Kit (3/4",1" & 1-1/2") Spring Kit (2") 1-1/2" x 3/4" Reducer Bushing 1- 1/2" Cap Assembly 2" Cap Assembly

ABOVE GROUND TANK VALVES

SOLENOID VALVES

Application -

Reducing fire hazards and fuel spillage should a line rupture. The valve opens when energized from a dispenser or pump switch.

Part Number - 404V



Heavy duty two way normally closed, one directional flow. Piston style design for High Flow, and zero differential.

Features -

Inrush

- ✓ Zero Differential Direct Lift
- ✓ Higher Flow than Diaphragm Valves
- ✓ Internal Pressure Relief
- ✓ No need to specify 120V/60 or 24V/DC when ordering

Other sizes and materials available. Call for more information.

2.0

Construction -

- Brass Body & Piston
- FKM seals



Safety Valve for Hazardous Location E510184

| Pipe Size (inch) | Part Number | Orifice Size | Cv Flow Factor | Pre | rating ssure ntial (PSI) | Max Fluid | Watt F | Rating/ ation |
|---------------------|---------------------|-----------------|-------------------|-----|--------------------------------|--------------|--------|------------------|
| | | (mm) | - 8 | Min | Max | Temp (F) | AC | DC |
| 1-1/2" | 404V-15-120/60-24DC | 38 | 19 | 0 | 100 | 180 | 30/H | 48/H |
| 2" | 404V-20-120/60-24DC | 38 | 27 | 0 | 100 | 180 | 30/H | 48H |

 Current Draw (amps):

 Volt/Hz
 120/60
 24/DC

 Holding
 0.66
 2.0

2.23

Important Installation Instructions: A strainer or a filter (100 microns) is recommended to be installed as close as possible to the inlet of the valve. The valve can only be installed in the horizontal position with coil vertical and upright,

CAPS

PIPE CAP

Application -

Capping pipe in extractor valve assemblies, storage tanks, and monitoring wells.

Part Number - 412




Features -

- ✓ A convenient cross bar for easy removal and installation
- ✓ Rugged metal construction

Construction -

- All cast aluminum
- · Plated steel cross bar
- · Buna-N gasket

| | Thread | | | |
|--------|--------|---------------|------|----|
| Model | Size | Weight (lbs.) | Α | В |
| 412-40 | 4" | 1.2 | 2.5" | 4" |



Replacement Parts

| Part Numbers | Description |
|--------------|-------------|
| 412-4-B | Groove Pin |
| 724-44-B | Gasket |

CAPS

DUST CAP FOR 4" PIPE

Application -

Capping pipes in extractor valve assemblies, storage tanks, and monitoring wells.

Part Number - 418



Model 418

Model 418TM



Only from Universal! — The 418TM-40 is easy to install and remove, because of the top ears configuration. Ribbing on the side allows easy hand tightening.


Features -

- ✓ Top mounted ears allow easy removal and installation
- Rugged construction for long life
- ✓ Durable and non-corrosive
- ✓ Liquid tight seal
- ✓ UL#E79903
- ✓ CSA#LR50370-10 approved

Construction -

- · Reinforced composite plastic construction
- · Buna-N seal

| | Thread | C | able Gripping |
|--------------|--------|---------------|---------------|
| Model | Size | Weight (lbs.) | Range |
| 418-40 | 4" | 0.5 | - |
| 418TM-40 | 4" | 0.5 | .138315 |
| 418TM-40-125 | 4" | 0.5 | .079236 |
| 418TM-40-15 | 4" | 0.5 | .197472 |



Replacement Parts Part Numbers Description

| 418-4-B | Gasket |
|-----------|---------------------|
| 418TM-4-A | 3/8" Cord Connector |
| 418TM-4-B | 1/2" Cord Connector |
| 418TM-4-C | 1/8" Cord Connector |


EXTRACTOR FITTINGS

EXTRACTABLE CHECK VALVES

Application -

Holds prime in suction system applications.

Part Number - 515





Strategically used in place of foot valves.

ONLY UNIVERSAL HAS A

METAL-TO-METAL BRASS SEAL.

Features -

- ✓ Holds the prime
- Easily serviced without disturbing existing pipes in suction systems
- ✓ No need to remove valve to clean because it has a removable front plate for easy maintenance
- ✓ Rugged cast iron body eliminates distortion of valve seat when tightened

A

Construction -

· Zinc plated cast iron body

| Model | Thread Size | Weight (lbs.) | Α | В | Seal |
|----------|-------------|---------------|---------|--------|---------------------------|
| 515B-15 | 1-1/2" | 8.5 | 5-3/16" | 4-7/8" | Buna-N |
| 515BS-15 | 1-1/2" | 8.5 | 5-3/16" | 4-7/8" | Buna-N w/ strainer |
| 515M-15 | 1-1/2" | 8.5 | 5-3/16" | 4-7/8" | Metal-to-Metal |
| 515MS-15 | 5 1-1/2" | 8.5 | 5-3/16" | 4-7/8" | Metal-to-Metal w/strainer |

Replacement Parts

| Part Numbers | Description |
|--------------|--------------------------------|
| 0611V-34-B | 5/16" Bolt |
| 515-15-10 | Cone Spring |
| 515-15-7 | Cover Gasket |
| 515-15-8 | Cage Gasket |
| 515-15-9 | Strainer |
| 515-CAB | Cage Assembly (Buna-N) |
| 515-CAM | Cage Assembly (Metal to Metal) |



VAPOR RECOVERY-ADAPTER CHECK VALVE

Application -

Returning vapor back to the tank truck during a product drop. A poppeted valve seals vapor tight when uncoupled.

Part Number - 0611V




Features -


- ✓ Compatible with Universal caps 0613VC and 0614VC
- ✓ Corrosion resistant hard coated aluminum cast body
- ✓ Maximum working pressure rated at 10 PSI

Construction -

- Hard coated aluminum casting
- Buna-N gasket
- Stainless steel stem
- Aluminum stem guide
- Stainless steel spring

| Model | Size | Weight (lbs.) | Α | В |
|------------|---------|---------------|--------|-----------------|
| 0611V-3040 | 3" x 4" | 3.2 | 5-1/2" | 5 - 5/8" |
| 0611V-3030 | 3" x 3" | 3.2 | 5-1/2" | 5-5/8" |





Replacement Parts Part Numbers Description

724-44-B Gasket



VAPOR RECOVERY FLAT TOP CAP

Application -

Low profile which extends only 5/8" above the adapter, allows maximum clearance in manhole, and has a total water and vapor seal solution.

Part Number - 0613VC





Only from Universal! - A low profile design which allows for maximum clearance. This compensates for ground heaving and settling. Our cam-action cap produces a water and vapor tight total seal solution. Truly the best in the industry.

Features -

- ✓ Cam-action handle provides a total water and vapor seal solution
- ✓ Non-corrosive polymeric coating
- ✓ Color-coded in "orange" for easy recognition and maintenance
- ✓ Compatible with 0611V Vapor Check Valve Adapter
- ✓ Compatible with E-85


Construction -

- Cast aluminum body
- · Ductile iron cam-action handle
- Buna-N seal

| Model | Size | Weight (lbs.) | Α | В |
|-----------|------|---------------|----|-----------------|
| 0613VC-30 | 3" | 3,6 | 4" | 7 - 1/2" |

Replacement Parts Part Numbers Description

0613VC-3-B Gasket







VAPOR RECOVERY-TOGGLE LEVER CAP

Application -

A lockable toggle-action cap provides a positive uniform seal.

Part Number - 0614VC



Features -

- ✓ Positive uniform seal
- ✓ Non-corrosive polymeric coating
- ✓ Color-coded in "orange" for easy recognition and maintenance
- ✓ Compatible with Universal 0611V adapter
- ✓ Compatible with E-85

Construction -

- Cast aluminum body
- · Zinc plated steel arms
- · Bronze cam action levers
- · Stainless steel pivot pins
- · Buna-N seal

| Model | Size | Weight (lbs.) | Α | В |
|-----------|------|---------------|--------|----|
| 0614VC-30 | 3" | 1.7 | 2-7/8" | 7" |


Replacement Parts

Part Numbers Description

731-4-C Gasket



Only from Universal! - The ultimate in quality. Rugged cast aluminum for added strength and long-life durability, unlike competitive companies who use only plastics, which may crack or break under normal use.





DROP TUBES & ACCESSORIES

THE RAG STOPPER

Application -

The Rag Stopper is designed to prevent debris from entering the storage tank during filling. Saves on expensive recurring maintenance fees.

Part Number - RAGSTOPPER




Features -

- ✓ Universally compatible with all 4" fill adapters*
- ✓ All fueling operations remain the same. No fuel restrictions
- ✓ Prevents debris from entering the fuel tank
- ✓ Allows for use of gauge stick
- ✓ Prevents fuel theft by blocking the stinger from entering the tank

Construction -

- Carbon steel body
- Buna-N Seal



*Does not work with coaxial



Notice: Universal Valve Co., products must be used in compliance with applicable federal, state, and local laws and regulations. Product selection should be based on physical specifications and limitations and compatibility with the environment and material to be handled. Universal Valve Co., makes no warranty of fitness for a particular use. All illustrations and specifications in this literature are based on the latest production information available at the time of publication. Prices, materials, and specification are subject to change at any time, and models may be discontinued at any time, in either case, without notice or obligation.



TOP SEAL ADAPTERS

Application -

Threads onto the fill pipe by means of internal wrenching lugs. Compatible with Universal 731 and 733 caps.

Part Number - 724



Features -

- ✓ Compatible with Universal 731 and 733 caps
- ✓ Rugged and durable casting
- ✓ Compatible with E-85

Construction -


- · Bronze construction
- Buna-N gasket

| Model | Cap Size | Pipe Size | Weight (lbs.) | Α | В |
|----------|----------|-----------|---------------|--------|--------|
| 724-4040 | 4" | 4" | 2.6 | 2-3/4" | 4-7/8" |
| 724-3030 | 3" | 3" | 2.0 | 1-3/4" | 3-3/4" |
| 724-3040 | 3" | 4" | 2.0 | 2-1/2" | 4-7/8" |

Replacement Parts

| Part Numbers | Description |
|--------------|---------------------|
| 724-44-B | Gasket (Models 724) |

Notice: Universal Valve Co., products must be used in compliance with applicable federal, state, and local laws and regulations. Product selection should be based on physical specifications and limitations and compatibility with the environment and material to be handled. Universal Valve Co., makes no warranty of fitness for a particular use. All illustrations and specifications in this literature are based on the latest production information available at the time of publication. Prices, materials, and specification are subject to change at any time, and models may be discontinued at any time, in either case, without notice or obligation.



UNIVERSAL VALVE COMPANY

COAXIAL ADAPTERS TOP SEAL

Application -

Threads onto the fill pipe. Includes a set screw to reduce movement on the riser pipe. Compatible with Universal 731 and 733 caps.

Part Number - 724CA



Features -

- ✓ Hard coated aluminum construction for added corrosion protection
- Compatible with Universal 731 and 733 caps

Construction -


- · Hard coated aluminum casting
- · Stainless steel set screw

| Model | Size | Weight (lbs.) | A | В |
|------------|---------|---------------|--------|--------|
| 724CA-4040 | 4" x 4" | 1.6 | 4-1/8" | 5-1/8" |

Replacement Parts

Part Numbers Description

724CA-44-B Set screw (Model 724CA-4040)



ADAPTER WRENCHES

Application -

Used where a wrench is needed to secure or remove a fill, cap, extractor, vapor adapter, tank risers and or turbines

Part Number - 724, 410W, 0611, V423-EXT



Features -

- √ 724-7W removes and installs fill adapters (724, 724A) 1-5/16" socket
- ✓ 0611V-W removes and installs vapor and coaxial adapters (0611V, 724CA)
- ✓ 410W removes and installs extractor fittings and pipe caps (412-40, V423)
- ✓ V423-EXT removes extractor fitting with damaged pins

Construction -

- 0611V-W, 410W and V423-EXT all steel
- · 724-7W Cast Iron

| Model | Weight (lbs.) | Height | Width/Diameter |
|----------|---------------|--------|----------------|
| 724-7W | 2.00 | 2.50" | 6.25" |
| 410W | 7.50 | 52.00" | 1.95" |
| 0611V-W | 13.00 | 42.25" | 6.37" |
| V423-EXT | 19.00 | 54" | 3" |

FILL ADAPTER CAP

Application -

A lockable cap to provide uniform seal.

Part Number - 726



Features -

√ 726-30 compatible with 724-3030 and 724-3040


Construction -

- · Bronze construction
- Buna-N Gasket

| Model | Size | Weight (lbs.) | Α | В |
|--------|------|---------------|-------|-------|
| 726-30 | 3" | 1.50 | 2.00" | 5.00" |

Replacement Parts

| Part Numbers | Description | |
|--------------|-------------|--|
| 726-3-C | Gasket | |





FLAT TOP CAP TOP SEAL

Application -

Low profile which extends only 5/8" above the adapter, allows maximum clearance in manhole. Provides a total seal.

Part Number - 731




Features -

- ✓ Water and vapor tight cam-action handle
- ✓ Color-coded in "gray" for easy recognition and maintenance
- ✓ Compatible with 724 and 724CA adapters
- ✓ Non-corrosive polymeric coating
- ✓ Compatible with E-85

Construction -


- · All aluminum cast cap
- · Ductile cast iron handle
- Buna-N Seal

| Model | Cap Size | Weight (lbs.) | Α | В |
|--------|----------|---------------|----|----|
| 731-40 | 4" | 3.5 | 4" | 7" |





Only from Universal - a special low profile design allows for maximum clearance in manhole installations to compensate for ground heaving and settling. Our cam-action cap and handle design combines with the gasket to produce a water and vapor tight total seal solution. Truly the best in the industry.







TANK MONITOR CAP AND ADAPTER KITS

Application -

Cap and adapter for leak detection systems. Available with 3/8" or 1/2" thread hole. Kit comes equiped with 731 Flat Top Cap or 733 Toggle Cap, 725 adapter and your choice or cord connectors...The Cap is lockable and the adapter has no lugs for full riser access.

Part Number - 731TMK & 733TMK





Now Available in a Toggle Cap or Heavy Duty Flat Top Cap

Features -

- ✓ Toggle action provides a positive, uniform seal
- ✓ Non-corrosive polymeric coating and aluminum casting
- ✓ Color-coded in "gray" for easy recognition
- ✓ Compatible with E-85

Construction -

- · Cast aluminum
- · Zinc plated steel arms
- · Stainless steel cam-action levers
- · Stainless steel pivot pins
- · Buna-N seal

| Model | Description |
|---------------|--|
| 731TMK-40 | TM Cap and Adapter w/3/8" threaded hole and 3/8" Grip Cord Con |
| 731TMK-40-125 | TM Cap and Adapter w/3/8" threaded hole and 1/4" Grip Cord Con |
| 731TMK-40-15 | TM Cap and Adapter w/1/2" threaded hole and 1/2" Grip Cord Con |
| 733TMK-40- | TM Cap and Adapter w/3/8" threaded hole and 3/8" Grip Cord Con |
| 733TMK-40-125 | TM Cap and Adapter w/3/8" threaded hole and 1/4" Grip Cord Con |

^{*}Available Cap only 731TM - & 733TM-



TOP SEAL/TOGGLE LEVER CAP

Application -

A lockable cap with toggle action to provide a positive uniform seal. Fits all top seal adapters.

Part Number - 733



Features -

- ✓ Toggle action provides a positive, uniform seal
- ✓ Non-corrosive polymeric coating and aluminum casting
- ✓ Color-coded in "gray" for easy recognition
- ✓ Compatible with Universal 724 and 724CA adapters
- ✓ Compatible with E-85

Construction -

- · Cast aluminum
- · Zinc plated steel arms
- · Stainless steel cam-action levers
- · Stainless steel pivot pins
- · Buna-N seal

731-4-C


| Model | Cap Size | Weight (lbs.) | Α | В |
|--------|----------|---------------|--------|----|
| 733-40 | 4" | 1.7 | 2-7/8" | 7" |

Replacement Parts Part Numbers Description

Gasket



Only from Universal! - All aluminum cast cap for added strength, long-life and maintenance free use, unlike competitive plastic caps which, may crack under pressure.





LIQUID TIGHT FUEL BOXES

FLUSH MOUNT FILL BOX

Application -

Mounts flush to connect the underground tank fill line to the surface, without a manhole enclosure.








Features -

- ✓ Ideal for fuel, oil, waste oil, and diesel fuel applications
- ✓ Designed to withstand heavy driveway traffic
- ✔ Recommended for applications not requiring security or containment

Construction -

- · A threaded bronze cover
- · Heavy duty cast iron body
- · Buna-N gasket

| Model | Thread Size | Weight (lbs.) | Α | В |
|--------|-----------------|---------------|--------|--------|
| 701-20 | 2" | 2.3 | 2-1/8" | 3-5/8" |
| 756 | Multi-purpose | | | |
| | fill box wrench | 2.4 | | |



Replacement Parts

| Part Numbers | Description |
|--------------|----------------|
| 701-2-B | 2" Cap |
| 701-2-C | 2" Buna Gasket |

PIPE LINE ACCESSORIES

PIPE EXTENSIONS

Application -

Compensates for ground heaving and settling in existing installations. It is recommended for all new installations, to add height to the riser pipe.

Part Number - 1002





A Universal first for over 25 years! Used to compensate for ground heave, eliminating the need to field cut pipe as tank rises.


Features -

- ✓ May be used for all adapters
- ✓ Easily retro-fits after installation
- ✓ Eliminates field cut pipe

Construction -

· Cast iron body

| Model | Size | Weight (lbs.) | Α | В |
|----------|---------|---------------|--------|--------|
| 1002S-40 | 4" x 4" | 2.5 | 2-1/2" | 1-3/4" |
| 1002L-40 | 4" x 4" | 3.6 | 3-1/2" | 2-1/2" |



VALVE FITTINGS & ACCESSORIES

DOUBLE POPPET SAFETY VALVES

Application -

Maximum safety in a double-poppet safety valve with two independent seals.

Part Number - 521DP, 522DP





The Safest Safety Valve! Only Universal uses an independent shear section for easy replacement. No need to remove the top poppet as with competitive products. Also, no need to buy an expensive replacement poppet top. This reduces the chance of fire and contamination. This unique three piece design allows for two independent seals which increases safety and reduces future labor and replacement costs.

<u>Features -</u>

- Pressure relief (upper poppet) to prevent pressure build-up
- Both poppet and seats are completely independent of the shear section, so when sheared the valve assures a 100% liquid tight seal
- ✓ The single link design provides ease of operation and reduced maintenance
- ✓ An air test port allows line testing without breaking the integrity of the line
- Raised bosses provide secure anchoring
- Optional model 522DP with 2" external male threads for easy connection to secondary containment piping

Construction -


- Zinc-plated/ E-Coated cast iron body and top
- · Stainless steel spring, shaft, and reset nut
- Buna-N seal

VALVE FITTINGS & ACCESSORIES

DOUBLE POPPET SAFETY VALVES (CONTINUED)

| Model | Top Thread | Size | Weight (lbs.) | Α | В | С |
|-------------|-----------------|--------|---------------|--------|--------|--------|
| 521DP-RF-15 | Female | 1-1/2" | 7.0 | 2-3/4" | 4-1/2" | 8-1/4" |
| 521DP-RM-15 | Male | 1-1/2" | 7.0 | 2-3/4" | 4-1/2" | 8-1/4" |
| 522DP-RF-15 | Fema l e | 1-1/2" | 7.0 | 2-3/4" | 4-1/2" | 8-1/4" |
| 522DP-RM-15 | Male | 1-1/2" | 7.0 | 2-3/4" | 4-1/2" | 8-1/4" |

Should an original Universal Double-Poppet Safety Valve be sheared or its top become damaged, Universal offers replacement tops and shear sections, which can be ordered separately.



Replacement Tops -

| Model | Description |
|---------------|-----------------------------|
| 521DP-RF-15-C | Female Double Poppet Top |
| 521DP-RM-15-B | Male Double Poppet Top |
| 521DP-SS-15 | Double Poppet Shear Section |

Accessories -

Universal also offers the model #521KR "Sure Shear"™ U-Clamp Anchor, which conforms to NFPA-30, and <u>assures positive shearing action upon severe impact.</u> It fits all major industry safety valves, and is easy to install in both new and retro-fit applications.

Replacement Parts

| Part Numbers | Description |
|--------------|-----------------------|
| 520R-1-2 | 3/8" Plug |
| 520R-1-8 | Body to Top Seal Ring |
| 521R-15-H | Fusible Link |
| 521R-15-I | Reset Nut |
| 521R-5/16-18 | 5/16" Bolt |


VALVE FITTINGS & ACCESSORIES

SINGLE POPPET SAFETY VALVES

Application -

Maximizes safety, and prevents fuel spillage and fire hazard.

Part Number - 521, 522





Only from Universal! The safest safety valve! The poppet and seat are completely independent of the top shear section, so even with the top off, the valve assures a 100% liquid tight seal.

Features -

- ✓ A 100% seal
- ✓ Unobstructed flow
- ✓ The poppet and seat are completely independent of the top shear section, so even with the top off, the valve assures a 100% liquid tight seal
- ✓ The single-link design provides ease of operation and reduced maintenance
- ✓ A stainless steel reset nut eliminates stripping the fusible link during valve reset, reducing downtime by allowing manual reset even under pressure
- ✓ All Universal Safety Valves are protected by zinc plating, assuring maximum corrosion resistance, unlike competitive products that are only painted
- ✓ An air test port allows line testing without breaking the integrity of the line
- Raised bosses provide secure anchoring

Construction -

- Zinc-plated/ E-Coated cast iron body and top
- · Stainless steel spring and shaft
- Bun-N seal

VALVE FITTINGS & ACCESSORIES

SINGLE POPPET SAFETY VALVES (CONTINUED)

| Model | Top Thread | Size | Weight (lbs.) | Α | В | С |
|-----------|-----------------|--------|---------------|--------|--------|------------------|
| 521RFS-15 | Fema l e | 1-1/2" | 5.2 | 2-3/4" | 4-1/2" | 6-3/8" |
| 521RMS-15 | Male | 1-1/2" | 5.3 | 2-3/4" | 4-1/2" | 6-13/16" |
| 521RUS-15 | Union | 1-1/2" | 6.3 | 2-3/4" | 4-1/2" | 7 - 5/16" |
| 522RFS-15 | Female | 1-1/2" | 5.2 | 2-3/4" | 4-1/2" | 6-3/8" |
| 522RMS-15 | Male | 1-1/2" | 5.3 | 2-3/4" | 4-1/2" | 6-13/16" |
| 522RUS-15 | Union | 1-1/2" | 6.3 | 2-3/4" | 4-1/2" | 7 - 5/16" |

UNIVERSAL VALVECO ELIZABETH NJ.

Should an original Universal Safety Valve be sheared, or it's top become damaged, Universal offers replacement tops.

Replacement Tops -

| Model | Description |
|------------|------------------------------|
| 521RF-15-C | Female Single Poppet Top |
| 521RM-15-B | Male Single Poppet Top |
| 521RU-15-D | Single Poppet With 2/3 Union |

Replacement Parts

| Part Numbers | Description |
|--------------|-----------------------|
| 520R-1-2 | 3/8" Plug |
| 520R-1-8 | Body to Top Seal Ring |
| 521R-15-H | Fusible Link |
| 521R-15-I | Reset Nut |
| 521R-5/16-18 | 5/16" Bolt |



SAFETY VALVES

"SURE-SHEAR" U-CLAMP ANCHOR

Application -

Secures any remote pump safety valve, conforming with NPFA Code 30.

Part Number - 521KR



Only From Universal! A quick, easy and permanent way of mounting a safety valve. Saves time and money in anchoring.

Features -

- ✓ For retro-fit and new installations
- ✓ Eliminates need for expensive pump boxes or stabilizer kits
- ✓ Quick, easy and permanent
- ✓ Fits any major safety valve
- ✓ Saves time and money in anchoring
- ✓ Assures positive shearing action during accidental impact
- ✓ A securely anchored valve conforms with NPFA Code-30
- ✓ Compatible with E-85

Construction -

- · Rugged plated cast iron body.
- · Plated steel bolts, U-Clamp and hardware

| Model | Size | Min. | Max. | Weight (lbs.) | Α | В | С | D |
|------------|-----------|------|---------|---------------|--------|--------|--------|------|
| 521KR-8012 | 8" - 12" | 8" | 11-3/4" | 4.0 | 5-1/8" | 2-1/8" | 1-3/8" | 1/2" |
| 521KR-1216 | 12" - 16" | 12" | 15-3/4" | 4.4 | 5-1/8" | 2-1/8" | 1-3/8" | 1/2" |
| 521KR-1822 | 18" - 22" | 18" | 21-3/4" | 5.0 | 5-1/8" | 2-1/8" | 1-3/8" | 1/2" |

Replacement Parts

| Part Numbers | Description |
|--------------|---------------------------|
| 521KR-B | U-Bolt |
| 521KR-C1 | Bracket Casting |
| 521KR-E-ASST | Assorted Nuts And Washers |
| 521KR-H4 | 4" Extension Bolt |
| 521KR-H6 | 6" Extension Bolt |



SPILL CONTAINMENT MANHOLES

AST INTERNAL DRAIN

Application -

Above ground applications designed to contain fuel spillage during tank filling.

Part Number - 76CD



Features -

✓ An internal drain design, no external connections

✓ All steel construction and polymeric coating provide added protection

✓ A lightweight watershed cover is lockable for added security

7 gallon capacity


✓ Low profile design

- ✓ Threads onto a 4" riser
- V model without drain

Construction -

- · All steel construction with epoxy coating
- · Non-corrosive polymeric coating
- · Brass drain valve

| Interna | al drai | n \ | \ |
|---------|---------|------------|---|




| Model | Gallon Capacity | Weight (lbs.) | A | В | С | |
|-------------|--------------------|---------------|-----|--------|-----|--|
| 76CD-1608 | 7 | 32 | 20" | 8-1/4" | 12" | |
| 76CD-1608-V | 7 | 32 | 20" | 8-1/4" | 12" | |

Replacement Parts

| Part Numbers Descript |
|-----------------------|
|-----------------------|

| 70CD-12-15 | Screen |
|------------|----------------------|
| 70CD-12-DA | Drain Valve Assembly |
| 70CD-12-L | Knob for Drain Valve |
| 76-A | Tank |



Low profile design

Cap

Adapter



OVERFILL PROTECTION

AST 31/2 GALLON CONTAINMENT

Application -

Above ground applications designed to contain fuel spillage during tank filling.

Part Number - 76






Features -

- All steel construction and polymeric coating providing added protection
- A lightweight watershed cover is lockable for added security
- ✓ 3-1/2 gallon capacity
- ✓ Low profile design
- ✓ Threads into 2" NPT opening
- ✓ Internal and external 2" male coupling
- ✓ Compatible with E-85

Construction -

- · All steel construction with epoxy coating
- · Non-corrosive polymeric coating

| Model# | Gallon Capacity | Weight (lbs.) | Α | В |
|---------|--------------------|---------------|-------|-------|
| 76-35M | 3-1/2 | 11 | 10.5" | 11.5" |
| 76-35MS | 3-1/2 | 11 | 6" | 13" |





ABOVE GROUND MANHOLES

REMOTE FILL/LOCKING FILL BOX

Application -

AST remote fill requirements.

Part Number - 76RF





Only from Universal! - A superior single post design allows for easy adjustment during installation. A round top structure eliminates snow and rain build-up.


Features -

- Single pedestal design with one telescoping pipe allows for proper height adjustment
- ✓ Fast installation
- ✓ Round top structure, eliminates all snow and rain build-up
- ✓ Easy draining, with the round contour bottom to eliminate any liquid build-up
- ✓ All steel construction, for rugged strength and security
- Locking cover, provides security at tank to assure no unauthorized entry
- ✓ Epoxy coating resists hydrocarbons for long life
- ✓ Compatible with E-85

Construction -

- Epoxy coated 12 gauge steel container
- Buna-N seal

| Model | Pipe | Gallon Capacity | _ | Α | В | С |
|------------------|------|--------------------|----|------------|-----|-----|
| 76RF-02 | 2" | 8 | 72 | 42" to 52" | 17" | 18" |
| 76RF-03 | 3" | 8 | 72 | 42" to 52" | 17" | 18" |
| 76RF - 04 | 4" | 8 | 72 | 42" to 52" | 17" | 18" |



Replacement Parts

| Part Numbers | | Description |
|--------------|-----------|--------------------|
| | 76RF-08 | 4" Grommet |
| | 76RF-12 | 3/4" Ball valve |
| | 76RF-2-G | 2" Grommet Kit |
| | 76RF-3-G | 3" Grommet Kit |
| | 76RF-A | Tank and base only |
| | 6000-1-16 | Handle |
| | | |


IDENTIFICATION MARKERS

PIPE CLAMP MARKER

Application -

Color-coded identification with all API specifications for quick visual identification of underground stored fuel products

Part Number - 56




Features -

- ✓ Color-coded to API specifications
- ✓ Identification markers may be replaced or changed as needed
- ✓ Easy to install for retro-fit use
- ✓ Available for special applications
- ✓ Custom wording available. Call factory for details. Model "56-S"

Construction -

- Stainless steel band
- Aluminum marker tab
- · Plastic identification plate



| Model | Description | Weight (lbs. |) | Model | Descri | ption | Weight (lbs.) |
|--------|--------------------|--------------|-----|---------------|--------|----------------------|---------------|
| 56-B | Blank | | 0.5 | 56-RUE | "Regul | ar Unleaded w/Ethand | ol" 0.5 |
| 56-D | Diesel | | 0.5 | 56-S | Custon | n Marker | 0.5 |
| 56-E | Ethanol | | 0.5 | 56 - + | "+" Ma | rker | 0.5 |
| 56-E85 | "E85" Pipe Clamp M | 1arker | 0.5 | 56-UE | "Unlea | ded w/Ethanol" | 0.5 |
| 56-FO | Fuel Oil | | 0.5 | 56-ULT | Ultra | | 0.5 |
| 56-HO | Heating Oil | | 0.5 | 56-UP | Unlead | led Plus | 0.5 |
| 56-K | Kerosene | | 0.5 | 56-VR | Vapor | Recovery | 0.5 |
| 56-P | Premium | | 0.5 | 56-WO | Waste | Oil | 0.5 |
| 56-PU | Premium Unleaded | | 0.5 | | | | |
| 56-R | Regular | | 0.5 | Replace | ment E | Parte | |
| 56-SU | Super Unleaded | | 0.5 | Part Numi | | Description | |
| 56-U | Unleaded | | 0.5 | 56-1-A | DC13 | Bracket | |
| 56-M | Midgrade | | 0.5 | 56-C1 | | Screw For Marker | |
| 56-MU | Midgrade Unleaded | | 0.5 | 56-D1 | | Band | |
| 56-RU | Regular Unleaded | | 0.5 | JU-D I | | Danu | |



Custom Marker Tag Ordering Procedure:

- 1. Select 53-S (Round Marker) or 56-S (Rectangle Marker) -See catalog for details
- 2. Please note on your po: selected color from chart below. (Note stripe is the engraving color.)
- 3. Please note on your po: text wanted on marker (the more text the samller the font, we will do our best to fit everything and if we can't, we will let you know!)

For more information or any questions please call 800-223-0741 or e-mail sales@universalvalve.com



DROP TUBES AND ACCESSORIES

STICK PORT FLAPPER

Application -

Protects stick ports from accidental product drops.

Part Number - JH69




Features -

- ✓ Protects stick port from accidental product drops
- ✓ Works with model 724-4040
- ✓ Decal with large red lettering

Construction -

- · Stainless Steel
- Buna-N

| Model | Weight (Ibs.) | Α | В | С |
|--------|---------------|-------|------|------|
| JH69-4 | 1.25 | 4.25" | 1.5" | 1.5" |



ACCESSORIES - TRUCK STOPS

HOSECRADLE

Application -

Holds fueling hose at commercial truck stops in a pre-formed protective cradle to prevent hose collapse and kinking. Along with our 870 & 871 Hose Retriever, the HoseCradle creates a total system. Red with yellow safety harness provides for additional protection.

Part Number - 100HC





A Universal First – popular at all truck stops. It's curvature design <u>prevents</u> hose collapse by controlling how much the hose will bend during use.

Features -

- Extends life of fuel hoses
- ✓ Prevents hose damage
- ✓ Compatible with our #870& #871 hose retriever

Construction -

- Durable polyurethane construction
- · Metal clamps included

| Model | Size (Size determined by hose I.D.) | Weight (lbs.) |
|-----------|-------------------------------------|---------------|
| 100HC-100 | 1" (also fits 3/4" hose) | 2.8 |
| 100HC-125 | 1-1/4" | 3.25 |
| 100HC-150 | 1-1/2" | 3.5 |
| 100HC-200 | 2" | 4.0 |





ACCESSORIES - TRUCK STOPS

HOSE RETRIEVER

Application -

Keeping hoses suspended at truck stops and industrial sites. Protects hoses from excessive wear and damage. Prevents tangles and kinking. Reduces injury to customers from tripping accidents.




<u>Features -</u>

- ✓ Allows safe, easy fueling of trucks
- ✓ Head permits 360° rotation for total service in any direction
- ✓ Installs on a 20' length of 2" pipe
- Rugged cast iron body and weights
- ✓ Compatible with E-85

Construction -

- Cast iron head and body
- Stainless steel cable
- 2-10 lb. counterweights
- 20' of 1/8" aircraft cable
- · 2 adjustable hose clamps
- · Complete set of hardware
- · Pipe not included

Only from Universal! - The original is still the best! Installed at truck stops for over 50 years - this swivel head permits 360° rotation for easy service in any direction...saving and protecting hose by extending life, and eliminating expensive insurance claims from possible accidents.



Also Availble with HoseCradle. See price sheet for model numbers.

| Model | Height | Width | Weight (lbs.) |
|-------|--------|--------|---------------|
| 870 | 10" | 4-1/4" | 30 |

Replacement Parts

| Replacement Parts | | | | |
|-------------------|-----------------|--------------|-------------------------|---------|
| Part Numbers | Description | Part Numbers | Description | Ш |
| 521KR-E | 3/8" Nut | 870-7-8 | Hose Retriever | |
| 521KR-F | Lock Washer | | w/out Cable Weights | 4-4 |
| 870-7-1A | Weight Assembly | 870-7-II | Hose Clamp Assembly Kit | |
| 870-7-1 | Single Weight | 870-E | Stainless Steel Cable | |
| 870-7-3 | Base | 870-F | Cable Clamp | |
| 870-7-4 | Pulley | 870-M | Shoulder Bolt | unhaha |
| 870-7-6 | Ton Housing | 870-7-15 | Renair Kit | |



Hose Retriever

Bracket Bolted To The Dispenser

Counterweight

2" Pipe Stand - 6" Long

2" Pipe

HOSE RETRIEVER

HOSE RETRIEVER

Application -

Protects hoses from excessive wear and damage. Prevents tangles and kinking. Reduces injury to customers from tripping accidents. Equipped with a heavy-duty base eliminating the need to bury a 2" pipe.

Part Number - 871

871-Base + 870 = 871



Features -

- ✓ Eliminates the need to break concrete
- ✓ Head permits 360-degree rotation for total service in any direction
- ✓ Installs on a 2" Pipe up to 10'-6" tall
- Rugged cast iron body and weights
- Equipped with heavy-duty base and side bracket
- ✓ 20 lb. Counterweight
- ✓ Compatible with E-85

Construction -

- · Cast iron head and body
- · Stainless steel cable
- · Steel base


Model Weight (lbs.)


871 30


Replacement Parts

Part Numbers Description 871-BASE Foot Base

871-BRACKET Dispenser Bracket







Cable

HoseCradle

Notice: Universal Valve Co., products must be used in compliance with applicable federal, state, and local laws and regulations. Product selection should be based on physical specifications and limitations and compatibility with the environment and material to be handled. Universal Valve Co., makes no warranty of fitness for a particular use. All illustrations and specifications in this literature are based on the latest production information available at the time of publication. Prices, materials, and specification are subject to change at any time, and models may be discontinued at any time, in either case, without notice or obligation.

UNIVERSAL VALVE COMPANY

^{*}Also Availble with HoseCradle. See price sheet for model numbers.



HOSE RETRIEVER


HOSE RETRACTOR - COUNTERWEIGHT

Application -

Keeping conventional and Stage II vapor recovery coaxial hoses raised to prevent traps in the vapor line. Potential accidents are reduced. Hose life is greatly extended.

Part Number - 880/882









Only from Universal! - Our better looking profile blends in with today's modern dispensers.

Features -

- ✓ Easy to install and maintain
- Adaptable to most dispensers
- ✓ Corrosion resistant construction
- Long life with minimum service
- ✓ Plastic bushing minimizes cable wear

880 + 1" Clamp

✓ CARB certified

880-CS10

✓ Compatible with E-85

Now Available with Hose Clamps

Construction -

- 880 + 3/4" Clamp 880-CS34 880 + 3/4" & 1" Clamp Aluminum Post (2"x2") 880-CS34/10 882 + 1" Clamp Cast iron counterweight 882-CS10 882 + 3/4" Clamp Plastic bushings 882-CS34 882+ 3/4" & 1" Clamp Nylon Rope 882-CS34/10
- Includes both side and bottom mounting brackets

| Model | Weight (lbs.) | A | В | С | Counter Weight |
|-------|------------------|---------|--------|--------|-------------------|
| 880 | 29 | 78-3/4" | 5-1/2" | 2-1/4 | 20lbs |
| 882 | 38 | 92" | 5-1/2" | 2-1/4" | 27 l bs |

Č

Replacement Parts

| Part Numbers | Description | | | |
|---|--------------|----------|--|-------------------------------|
| 880-5 | Cover Pulley | 880-MBC | Square Brac | ket |
| 880-8 | Bushing | 880-WA | Weight Asse | embly (1-1/2" x 1-1/2") |
| 880-8A | Nylon Rope | 880-WA-2 | Weight Asse | embly (882) (1-3/4" x 1-3/4") |
| 880-A | Body | 880-AC | Body Assem | nbly |
| 880-B | Base | 880-CA | Cover Assembly | |
| 880-C | Cover | | Optional Hose Clamp Also Sold Separate | |
| | | | 100-CS10 | 1" ID Hose |
| *Custom heights and counterweights available. Call for options. | | | 100-CS34 | 3/4" ID Hose |

Notice: Universal Valve Co., products must be used in compliance with applicable federal, state, and local laws and regulations. Product selection should be based on physical specifications and limitations and compatibility with the environment and material to be handled. Universal Valve Co., makes no warranty of fitness for a particular use. All illustrations and specifications in this literature are based on the latest production information available at the time of publication. Prices, materials, and specification are subject to change at any time, and models may be discontinued at any time, in either case, without notice or obligation.

100-CS34

3/4" ID Hose

PIPE GUARDS

U-SHAPE GUARDS

Application -

Pipe guards used to protect property and expensive dispensers from traffic collisions.



Features -

Cost effective property and equipment protection

Construction -

- · Schedule 40 pipe
- Primed
- · Available in Stainless Steel (304-SS)

| Model | Description (Width is outside pipe dimension) | Weight (lbs.) |
|----------------|--|---------------|
| 1983-353656 | U-Shape Pipe Guard 3.5" OD x 36"w x 56"h | 70.00 |
| 1983-354153 | U-Shape Pipe Guard 3.5" OD x 41"w x 53"h | 70.00 |
| 1983-354850 | U-Shape Pipe Guard 3.5" OD x 48"w x 50"h | 70.00 |
| 1983-403656 | U-Shape Pipe Guard 4" OD x 36"w x 56"h | 86.00 |
| 1983-404153 | U-Shape Pipe Guard 4" OD x 41"w x 53"h | 86.00 |
| 1983-404174 | U-Shape Pipe Guard 4" OD x 41"w x 74"h | 130.00 |
| 1983-404354 | U-Shape Pipe Guard 4" OD x 43"w x 54"h | 86.00 |
| 1983-404851 | U-Shape Pipe Guard 4" OD x 48"w x 51"h | 86.00 |
| 1983-404951 | U-Shape Pipe Guard 4" OD x 49"w x 51"h | 86.00 |
| 1983-353656-SS | U-Shape Pipe Guard 3.5" OD x 36"w x 56"h | 70.00 |
| 1983-354153-SS | U-Shape Pipe Guard 3.5" OD x 41"w x 53"h | 70.00 |
| 1983-354850-SS | U-Shape Pipe Guard 3.5" OD x 48"w x 50"h | 70.00 |

^{*}Custom sizes available

PIPE GUARDS

U-SHAPE GUARDS WITH BASE PLATES

Application -

Pipe guards used to protect property and expensive dispensers from traffic collisions.

Part Number - 1983-PP



Features -

- Cost effective property and equipment protection
- ✓ Base Plates for easy mounting

Construction -

- Schedule 40 pipe
- Primed
- · Available in Stainless Steel (304-SS)

| Model | Description (Width is outside pipe dimension) | Weight (lbs) | Α | В | C |
|-------------------|--|--------------|------|-----|-----|
| 1983-353636-PP | U-Shape Bumper Guard 3.5" OD x 36" x 36" | 70 | 3.5" | 36" | 36" |
| 1983-353636-SS-PP | Stainless Steel U-Shape Bumper Guard 3.5" OD x 36" x 36" | 70 | 3.5" | 36" | 36" |
| 1983-354136-PP | U-Shape Bumper Guard 3.5" OD x 41" x 36" | 70 | 3.5" | 41" | 36" |
| 1983-354136-SS-PP | Stainless Steel U-Shape Bumper Guard 3.5" OD x 41" x 36" | 70 | 3.5" | 41" | 36" |
| 1983-354836-PP | U-Shape Bumper Guard 3.5" OD x 48" x 36" | 70 | 3.5" | 48" | 36" |
| 1983-354836-SS-PP | Stainless Steel U-Shape Bumper Guard 3.5" OD x 48" x 36" | 70 | 3.5" | 48" | 36" |
| 1983-403636-PP | U-Shape Bumper Guard 4" OD x 36" x 36" | 86 | 4.0" | 36" | 36" |
| 1983-404136-PP | U-Shape Bumper Guard 4" OD x 41" x 36" | 86 | 4.0" | 41" | 36" |
| 1983-404836-PP | U-Shape Bumper Guard 4" OD x 48" x 36" | 86 | 4.0" | 48" | 36" |

^{*}Custom sizes available

ACCESSORIES

BOLLARDS

Application -

Bollards are used to protect property and expensive dispensers from traffic collisions.

Part Number - 1984



Features -

✓ Cost effective property and equipment protection

Construction -

- · Schedule 40 pipe
- Primed
- Available in Stainless Steel (304-SS)

| Part Number | Diameter | Length |
|--------------|----------|--------|
| 1984-4063 | 4.0" | 63" |
| 1984-4072 | 4.0" | 72" |
| 1984-4084 | 4.0" | 84" |
| 1984-6063 | 6.625" | 63" |
| 1984-6072 | 6.625" | 72" |
| 1984-8084 | 8.625" | 84" |
| 1984-4063-SS | 4.0" | 63" |
| 1984-4084-SS | 4.0" | 84" |
| 1984-6063-SS | 6.625" | 63" |
| 1984-6084-SS | 6.625" | 84" |

ACCESSORIES


BOLLARDS WITH BASE PLATES

Application -

Bollards are used to protect property and expensive dispensers from traffic collisions.

Part Number - 1984-BP





Features -

- Cost effective property and equipment protection
- ✓ Base plates for easy mounting

Construction -

- Schedule 40 pipe
- Primed
- Available in Stainless Steel (304-SS)

| Model | Description | Weight (lbs) | Α | В |
|-----------------|-------------------------------------|--------------|--------|-----|
| 1984-4036-BP | Bollard 4" OD x 36" | 32 | 4" | 36" |
| 1984-4048-BP | Bollard 4" OD x 48" | 41 | 4" | 48" |
| 1984-4048-SS-BP | Stainless Steel Bollard 4" OD x 48" | 41 | 4" | 48" |
| 1984-4060-BP | Bollard 4" OD x 60" | 50 | 4" | 60" |
| 1984-4060-SS-BP | Stainless Steel Bollard 4" OD x 60" | 50 | 4" | 60" |
| 1984-6048-BP | Bollard 6" OD x 48" | 81 | 6.625" | 48" |
| 1984-6048-SS-BP | Stainless Steel Bollard 6" OD x 48" | 81 | 6.625" | 48" |
| 1984-6060-BP | Bollard 6" OD x 60" | 100 | 6.625" | 60" |
| 1984-6060-SS-BP | Stainless Steel Bollard 6" OD x 60" | 100 | 6.625" | 60" |

^{*}Custom sizes available

ACCESSORIES

BOLLARD COVERS

Application -

Bollard covers enhance and protect the appearance of bumper post steel bollards in all indoor and outdoor applications.

Part Number - 1984-BC




- 10 Standard colors
- ✓ 7 Reflective tape colors
- ✓ 8 Standard sizes for 4", 6", 8", & 10"
- ✓ Patented GripperTabs[™] installation is the fastest and easiest way to secure bollard covers

Construction -

- · 1/8" thick Polyethylene
- 3M #680 reflective tape

| Model | Description |
|-------------|-----------------------|
| 1984-BC452 | 4"x52" Bollard Cover |
| 1984-BC464 | 4"x64" Bollard Cover |
| 1984-BC752 | 7"x52" Bollard Cover |
| 1984-BC760 | 7"x60" Bollard Cover |
| 1984-BC772 | 7"x72" Bollard Cover |
| 1984-BC872 | 8"x72" Bollard Cover |
| 1984-BC1060 | 11"x60" Bollard Cover |



Colors Available

| Bollard Cover Colors: | | Tape Colors: | | |
|------------------------------|------|--------------|------|--|
| Red | (R) | Red | (R) | |
| Orange | (O) | Orange | (O) | |
| Yellow | (Y) | Yellow | (Y) | |
| Green | (G) | Green | (G) | |
| Blue | (B) | Blue | (B) | |
| White | (W) | White | (W) | |
| Brown | (BN) | Black | (BK) | |
| Tan | (T) | | | |
| Gray | (GY) | | | |
| Black | (BK) | | | |

ISLAND FORMS

ISLAND FORMS 6" RADIUS CORNERS

Application -

Island forms and curbing protect your most important equipment. Dispensers, ATM's, air machines, and much more. Designed to keep your dispenser equipment off of ground level to help keep water out of your dispenser sumps. Combine with Universal Pipe Guards and Bollards for maximum protection.

Features -

- Special slide cross braces require no field welding and are easily moved to accommodate many sump sizes
- Cost effective property protection

Construction -

- · 12 gauge steel
- · Primer coated black
- Available in Galvannealed Steel & Stainless Steel (304-SS)

Complete Island Form Kits:

(example: 3CK-430-SS 13" tall 4ft wide x 30ft long Stainless Steel)

End Caps:

(example: 3EC-4830-SS 13" tall 48" wide x 30" long Stainless Steel)



Side Rails:

2 = 9" Tall Width: 1ft increments 3 = 13" Tall up to 12 ft.

SR
Material: SS for Stainless Steel Empty for Galvannealed Steel

(example: 3SR-3-SS 13" tall 3 ft long Stainless Steel)



Cross Braces:

3CB- _____ Length: 36", 48", 60"

(example: 3CB-36 36" long cross brace)



ISLAND FORMS

ISLAND FORMS - FULL RADIUS ENDS

Application -

Island forms and curbing protect your most important equipment. Dispensers, ATM's, air machines, and much more. Designed to keep your dispenser equipment off of ground level to help keep water out of your dispenser sumps. Combine with Universal Pipe Guards and Bollards for maximum protection.

Features -

- Special slide cross braces require no field welding and are easily moved to accommodate many sump sizes
- ✓ Cost effective property protection

Construction -

- · 12 gauge steel
- · Primer coated black
- · Available in Galvannealed Steel & Stainless Steel (304-SS)

Complete Island Form Kits:

Material: SS for Stainless Steel Empty for Galvannealed Steel

(example: 3CK-FR430-SS 13" tall 4ft wide x 30ft long Stainless Steel)



End Caps:

3 = 13" Tall

EC-FR Length: 24", 30", 36" Material: SS for Stainless Steel
3 = 13" Tall 48", 60" Empty for Galvannealed Steel

in 1 ft increments

(example: 3EC-FR4830-SS 13" tall 48" wide x 30" long Stainless Steel)



Side Rails:

2 = 9" Tall Width: 1ft increments 3 = 13" Tall up to 12 ft.

SR
Material: SS for Stainless Steel Empty for Galvannealed Steel

(example: 3SR-3-SS 13" tall 3 ft long Stainless Steel)



Cross Braces:

3CB- ______ Length: 36", 48", 60"

(example: 3CB-36 36" long cross brace)



ISLAND FORMS

CURBING FORMS

Application -

Island forms and curbing protect your most important equipment. Dispensers, ATM's, air machines, and much more. Designed to keep your dispenser equipment off of ground level to help keep water out of your dispenser sumps. Combine with Universal Pipe Guards and Bollards for maximum protection.

Features -

Cost effective property protection

Construction -

- 12 gauge steel
- · Primer coated black
- · Available in Galvannealed Steel & Stainless Steel (304-SS)

Corner Pieces:

C2 = 9" Tall Width: 12", 18", 24"
3 = 13" Tall Width: 12", 18", 24"
Empty for Galvannealed Steel

(example: 2C-2423-SS 9" tall 24" x 24" Stainless Steel)

(example: 3SR-3-SS 13" tall 3 ft long Stainless Steel)



Side Rails:

2 = 9" Tall Width: 1ft increments 3 = 13" Tall up to 12 ft.

SR- — — — Material: SS for Stainless Steel Empty for Galvannealed Steel




BumperBoard™ U-Shaped Guard Mount

Application -

Increase profits by utilizing existing space on your pipe guards.

Promote in store specials at the pump with Universal's BumperBoard sign.

Part Number - 1999-2844



Features -

- Increase profits by utilizing existing space
- ✓ It's a fact that the average consumer takes 6 minutes to fuel their car you have their total attention
- ✓ Your customer will not miss your promotion as they pull up to the pump
- ✓ Mounts to standard bumper guard
- ✓ Easy front loading access for your message insert
- ✓ Rounded corners also available

Construction -

- · Powder coated aluminum frames
- · Heavy duty spring clips

| | | | | | Poster |
|-----------------|---|--------------|-------------------|----------|-------------|
| M <u>ode</u> l | <u>Description</u> | Weight (lbs) | Α | В | Insert Size |
| | BumperBoard 28" x 44" w/ ubolt mounting box | 22 | 29 -1 <i>/</i> 8" | 45 -1/4" | 28" x 44" |
| 1999-2844-2 | BumperBoard Secondary Sign 28" x 44" (no mounting bracket) | 14 | 29 -1 <i>/</i> 8" | 45 -1/4" | 28" x 44" |
| 1999-2844-RC | BumperBoard 28" x 44" w/ Rounded Corners w/u-bolt mounting box | 22 | 29 -1/8" | 45 -1/4" | 27" x 43" |
| 1999-2844-RC-2 | BumperBoard 28" x 44" w/ Rounded Corners Secondary Sign (no mounting bracket) |) 14 | 29 -1 <i>/</i> 8" | 45 -1/4" | 27" x 43" |
| 1999-2844-RC-MO | BumperBoard 28" x 44" w/ Rounded Corners w/ Murphy Oil u-bolt mounting box | 22 | 29 -1/8" | 45 -1/4" | 27" x 43" |
| 1999-U | U-bolt Mounting Box (formerly 1999-2844-U) Up to 4.5" O.D. pipe | 8 | | | |
| 1999-U-MO | U-bolt Mounting Box- Murphy Oil-w/special cover (formerly 1999-2844-U-MO) | 8 | | | |
| | | | | | |


BumperBoard™ Dual Bollard Mount


Application -

Increase profits by utilizing existing space between two bollards with Universal's dual bollard mount signage system.

Part Number - 1999-2844







Features -

- ✓ Increase profits by utilizing existing space
- It's a fact that the average consumer takes 6 minutes to fuel their car - you have their total attention
- ✓ Your customer will not miss your promotion as they pull up to the pump
- Mounts to dual bollards
- ✓ Easy front loading access for your message insert
- ✔ Rounded corners also available

Construction -

- Powder coated aluminum frames
- Heavy duty spring clips

| | | | | | Poster |
|----------------|---|--------------|----------|----------|-------------|
| Model | Description | Weight (lbs) | Α | В | Insert Size |
| 1999-2844-BM | Standard 28" x 44" Sign with Dual Bollard mounting Bracket (formerly 1999-BM-2) | 30 | 29 -1/8" | 45 -1/4" | 28" x 44" |
| 1999-2844-BM20 | Standard 28" x 44" Sign with Dual Bollard mounting Bracket Bollard Span (20"x38") | 15 | 29 -1/8" | 45 -1/4" | 28" x 44" |
| 1999-2844-2 | BumperBoard Secondary Sign 28" x 44" (no mounting bracket) | 14 | 29 -1/8" | 45 -1/4" | 28" x 44" |
| 1999-2844-RC-2 | BumperBoard 28" x 44" w/ Rounded Corners Secondary Sign (no mounting bracket) | 14 | 29 -1/8" | 45 -1/4" | 27" x 43" |
| 1999-BM | Dual Bollard Mounting Bracket Bollard Span (28" x 48") | 15 | | | |
| 1999-BM20 | Dual Bollard Mounting Bracket Bollard Span (20" x 38") | 15 | | | |


BumperBoard™ Single Bollard/Pole Mount

Application -

Increase profits by promoting utilizing existing space on bollards with Universal's single bollard mounting system.

Part Number - 1999-2844





Features -

- ✓ Increase profits by utilizing existing space
- It's a fact that the average consumer takes 6 minutes to fuel their car - you have their total attention
- ✓ Your customer will not miss your promotion as they pull up to the pump
- Mounts to round or square poles
- Easy front loading access for your message insert
- ✔ Rounded corners also available

Construction -

- · Powder coated aluminum frames
- · Heavy duty spring clips

| Model | Descri <u>pt</u> ion | Weight (lbs) | Α | В | Insert Size |
|----------------|---|--------------|----------|----------|-------------|
| 1999-2844 | BumperBoard 28" x 44" w/ ubolt mounting box | 22 | 29 -1/8" | 45 -1/4" | 28" x 44" |
| 1999-2844-2 | BumperBoard Secondary Sign 28" x 44" (no mounting bracket) | 14 | 29 -1/8" | 45 -1/4" | 28" x 44" |
| 1999-2844-RC | BumperBoard 28" x 44" w/ Rounded Corners w/u-bolt mounting box | 22 | 29 -1/8" | 45 -1/4" | 27" x 43" |
| 1999-2844-RC-2 | BumperBoard 28" x 44" w/ Rounded Corners Secondary Sign (no mounting bracket) | 14 | 29 -1/8" | 45 -1/4" | 27" x 43" |
| 1999-SQ | Square Pole Mounting Box (up to 5.25" o.d.) | 10 | | | |
| 1999-U | U-bolt Mounting Box (formerly 1999-2844-U) Up to 4.5" OD Pipe | 8 | | | |
| 1999-U-MO | U-bolt Mounting Box- Murphy Oil-w/special cover | 8 | | | |
| | (formerly 1999-2844-U-MO) Up to 4.5" OD Pipe | | | | |

THE WALLI™

Application -

Mounts to any window, wall or vertical space to highlight your offerings.

Part Number - 1999-Walli



UNIVERSAL ALVERIA

The Universal Sign System Strategically Brings Your Customer Into The Store...Ready To Spend...

Because It's The <u>ONLY</u> Sign System That Starts


At The Pump, And Finishes In The Store.

Features -

- Highlights your offers and specials
- Stops consumers and brings them into your store
- Enhances your fueling sites
- Available in standard or rounded corners
- ✓ Grabs attention and maximizes sales volume
- ✓ Standard size 28" x 44"
- Custom sizes available
- ✓ Easy front loading access for your message insert

Construction -

- · Powder coated steel frames
- · Heavy duty spring clips
- · Rounded corners also available



| Model# | Description | Weight (lbs.) |
|---------------|--|---------------|
| 1999-WALLI | 28" x 44" Wall mount sign | 14 |
| 1999-WALLI-RC | 28" x 44" Wall mount sign with rounded corners | s 14 |

INFLATORS

AIR TOWERS - FREE AIR

Application -

An Air Tower that is customizable to compliment all store designs.


Part Number - 1975-, 1975W







Universal's built tough air tower is designed to operate in high heat and freezing conditions.



Features -

- ✓ Rugged Construction
- ✓ Solid State timer
- ✓ 25 ft abrasion and weather resistent air hose
- ✓ Heavy duty tire pressure gauge
- ✓ 1/2 HP oilless compressor
- ✓ Maximum inflation of 100 psi.
- ✓ ETL Listed
- ✓ Stainless Steel Cabinet
- ✓ Painted Post (Optional Hot Dip Galvanized)
- ✓ All components UL listed

Construction -

- 16 Gauge metal housing
- Stainless steel
- Schedule 40 post

FREE AIR

1975-FA34-SS 1975-FA34-HR-SS 1975-FA34-HR-GSS 1975-FASV-SS

1975W-FA34-SS 1975W-FASV-SS

Description

Post mount Stainless Steel (painted hd-post)

Post mount Stainless Steel (painted hd-post)w/ Hose Reel Post mount Stainless Steel (Galvanized hd-post)w/ Hose Reel Post mount Stainless Steel Solenoid valve no internal Comp

(painted hd-post)

Wall mount Stainless Steel

Wall mount Stainless Steel Solenoid valve no internal Comp.

AIR INFLATORS

AIR TOWERS - COIN OPERATED

Application -

An Air Tower that is customizable to compliment all store designs.


Part Number - 1975-, 1975W







Universal's built tough air tower is designed to operate in high heat and freezing conditions.



Features -

- ✓ Rugged Construction
- ✓ Solid State timer
- ✓ 25 ft abrasion and weather resistent air hose
- ✓ Heavy duty tire pressure gauge
- ✓ 1/2 HP oilless compressor
- Maximum inflation of 100 psi.
- ✓ ETL Listed
- ✓ Stainless Steel Cabinet
- Painted Post (Optional Hot Dip Galvanized)
- ✓ All components UL listed

Construction -

- · 16 Gauge metal housing
- Stainless steel
- Schedule 40 post

Coin OperatedDescription1975-CO34-SSPost mount Stain

1975-CO34-HR-SS 1975-CO34-HR-GSS 1975W-CO34-SS 1975-CO34-SS-C

1975W-CO34-SS-C

Post mount Stainless Steel (painted hd-post)

Post mount Stainless Steel (painted hd-post)w/ Hose Reel Post mount Stainless Steel (Galvanized hd-post)w/ Hose Reel

Wall mount Stainless Steel

Post mount Stainless Steel w/ counter (painted hd-post)

Wall mount Stainless Steel w/ counter

AIR INFLATORS

AIR TOWERS REPLACEMENT PARTS

Air Tower Replacement Parts (71R642)

| Part Number | Description |
|--------------------------|---|
| 1975-14 | Tamper Proof Screw |
| 1975-14-TOOL | Tamper Proof Screwdriver |
| 1975-15 | Coin Timer |
| 1975-15-A | Free Air Timer |
| 1975-16 | Free Air Push Button |
| 1975-17 | Door Lock Assembly |
| 1975-19 | Air Hose |
| 1975-19M | Air Hose w/ metal braiding |
| 1975-20 | Tire Chuck and Gauge |
| 1975-22-SS | Wall mount Bracket |
| 1975-3 | Circuit Breaker |
| 1975-33 | Coin Box |
| 1975-33-F | Coin Box Funnel |
| 1975-37 | Air Pressure Adjustable Relief Valve |
| 1975-AIRST | "Air" Sticker |
| 1975-COCHASSIS-G | Complete Chassis Coin Operated -Gast Compressor |
| 1975-COISW | Coin Switch |
| 1975-COMPR-G | Air Compressor -Gast |
| 1975-COMP-TKIT | Compressor Conversion Kit |
| 1975-CYCOUNT | Cycle Counter |
| 1975-FACHASSIS-G | Complete Chassis Free Air -Gast Compressor |
| 1975-FRAR | "Free Air " Sticker |
| 1975-HDPOST | Heavy Duty Post assembly (Painted) |
| 1975-HDPOST-G 1975-HR | Heavy Duty Post assembly (Hot Dip Galv) Hose Reel |
| 1975-IN25 | "25 cents" Instruction Sticker |
| 1975-IN50 | "50 cents" Instruction Sticker |
| 1975-KEY | Door Key |
| 1975-LK | Heavy Duty Lock Kit |
| 1975-POST-SS | Post Assembly (Stainless Steel) -optional |
| 1975-STINS | "Instructions" Sticker for Free Air |
| 1975-WARN | "Warning" Sticker |
| 10/0 44/11114 | Walling Glonol |

Gast Compressor Replacement Parts (71R642)

| Part Number | Description | |
|---------------------|---|---|
| 1975 - 34G | Compressor Relief Valve -Gast Compressor | _ |
| 1975 - 35G | Air Compressor Air Filter-Gast Compressor | |
| 1975 - K557D | Gast Repair Kit | |

Gast Compressor Replacement Parts (87R642)

| Part Number | Description |
|-------------------|---|
| 1975 - 34G | Compressor Relief Valve -Gast Compressor |
| 1975 - 35G | Air Compressor Air Filter-Gast Compressor |
| 1975-K965 | 87R Gast Repair Kit |

WARRANTY

Universal's iron clad warranty is straight forward and fair. All of our products are guaranteed to be free from defects in materials. Our workmanship is second to none in the Petroleum Equipment Industry. This will continue to be one of the corner stones of Universal Valve Company, Inc.

LIMITED WARRANTY: All Universal products are thoroughly tested before shipment and guaranteed to the extent of replacing only products found to be defective in manufacture. Claims must be made within one year from date of invoice. We cannot, however, allow claims for labor or consequential damage resulting from purchase, installation or misapplication of our products.

CLAIMS: Our responsibility ceases when products are accepted by transportation carriers. All goods are at the risk of the purchaser after they have been delivered by us to the carrier and receipt obtained for same (in good order).

PRODUCT CHANGES: The right is reserved to make changes in pattern, design, or materials when deemed necessary, without prior notice. Products which have become obsolete by reason of design change, or discontinued as a manufactured item, may not be returned for credit.

PRICE CHANGES: Due to changes in design and manufacture, all prices listed herein are subject to change without notice.

THE STANDARD!



Bottom Line Performance.



www.universalvalve.com • Phone: (800) 223-0741 sales@universalvalve.com • Fax: (800) 443-8258







Your Industry Specialist



Consistent Quality Engineered Products



A Family Tradition Since 1932

www.universalvalve.com · 800-223-0741



Choose Universal!!

Manholes:



- Composite: H-25 Load Rated 25% stronger then the competitor!
- Composite: Fuel Resistant Resins
- Steel Manholes: True H20 load rated with ½" thick diamond plate.
- All Manholes: Flanged Bottom skirt eliminates deflection during concrete pour and acts as a 360-degree concrete block.
- All Manholes: Steel construction ring eliminates oblong ring during concrete pour.
- All Manholes: Made in the USA!

Island Forms:



- Easy alignment tabs for perfect seams
- Sliding Braces for no field welding
- Available in Primed Carbon steel and Stainless Steel
- Made in the U.S.A.


Pipe Guards:





- Schedule 40 structural pipe Never cheap tubing or inferior overseas pipe.
- Stainless Steel and Primed Carbon Steel
- Available in 3.5" and 4" OD pipe
- Custom Sizes available!
- Made in the U.S.A.

The Rag Stopper



Eliminate Expensive Submersible Pump Shutdowns Caused by Rags

Your Industry Specialist!



www.universalvalve.com 908.351.0606

UNIVERSAL VIVERSAL VIVERSAL

Your Industry Specialists



Universal Valve Company Inc. 478 Schiller St • Elizabeth, NJ 07206 1-800-223-0741 • (F) 1-800-443-8258 sales@universalvalve.com